

3PT. HITCH SPRAYER-3P50, 100, 200 GALLON



Pump, DP50- Model MP40, three buna diaphragms 10.5 gpm (39.6L), 425 psi (28.3 bar), @ 550 rpm. Anodized aluminum case. Internal moving parts sealed in oil. Mounted on sprayer frame.

Pump, DP100 & DP200- Model APS71, three buna diaphragms, 18.9 gpm (71.4L), 580 psi (40 bar) @ 550 rpm. Anodized aluminum case, internal moving parts sealed in oil. Pulsation dampner. Mounted on sprayer frame.

Cutoffs- Left, right, and center pressure outlets for booms and hand gun.

Relief Valve- Adjustable type with pressure release handle.

Pressure Gauge- DP50 - 0-860 psi (0-60 bar).
DP100/DP200 - 0-1150 psi (0-80 bar). Oil filled.

Suction Strainer-

DP50/DP100 - External with cutoff valve. Supplied with quick couple fill coupling.
DP200 - Internal tank mounted with cylindrical filter.

Power- PTO shaft driven.

Tank-

DP50/DP100 - Modular, fully-emptying, polyethylene with fluid agitation and suction filter. Includes hand-wash tank. Screw-on vented plastic lid with strainer basket. Tank level sight gauge (metric and U.S. measure).

DP200 - Polyethylene with fluid agitation via manifold inside tank. Screw-on lid with air vents. Plastic basket-type filler strainer. Tank level sight gauge (metric and U.S. measure). Handwash and foam marker reservoir.

Frame - Welded structure angle iron, hot dipped galvanized.

Boom Mounts - Angle iron, multi-height adjustments.

Three Point Hitch- Category 1 or 2.

Crating included.