## **CW Series**

Great for indoors! This powerful, electric belt drive series is the perfect solution for any industrial job requiring exhaust-free operation.

ELECTRIC - BELT DRIVE

PORTABLE



CW-2405-4ME1

**Pump:** Belt drive triplex piston General pump with ceramic plungers • Stainless-steel and brass unloader • Forged brass manifold • Thermal relief valve **Motor:** Totally enclosed fan-cooled electric motor with thermal overload protection • 10-foot power cord

**Frame:** Powder coated steel tube handles • 1/4-inch powder coated steel base plate • Hose wrap with gun/wand holder • Solid steel threaded axle • Pneumatic tires with tubes for longer life • Dual rubber isolators

**Component:** Heavy-duty dual cogged belt drive system and cast-iron pulleys **Accessories:** Quick connect nozzles (0°, 15°, 25° and 40°) - 50-foot x <sup>3</sup>/8-inch non-marking hose with quick connects, swivel and bend restrictors - Professional-grade insulated trigger gun with safety lock-off - 36-inch lance with rubber grip (48-inch lance on 4000- & 5000-PSI models)



External bypass system creates less heat build-




Water filter with clear sleeve for screen inspection



Totally enclosed powder coated steel belt guard

## **CW Series**

		PO	RTABLE			ELECT	RIC - E	BELT DRIVE
Model No.	PSI	GPM	HP/Motor	Plug Type	Dimensions (LxWxH)	Ship Wt.	Net Wt.	
CW-2405-4ME1	2400	4.6	7.5/230V, 1Ø, 35.7A	NEMA 6-50P	46in.x28in.x30in.	345 lbs.	333 lbs.	
CW-2405-4ME3*	2400	4.6	8.0/230V, 3Ø, 24.7A or	NEMA L15-30P	46in.x28in.x30in.	255 lbs.	243 lbs.	
			8.0/460V, 3Ø, 11.5A					
CW-3004-4ME1	3000	3.5	7.5/230V, 1Ø, 35.0A	NEMA 6-50P	46in.x28in.x30in.	350 lbs.	338 lbs.	
CW-3004-4ME3*	3000	3.5	8.0/230V, 3Ø, 23.0A or	NEMA L15-30P	46in.x28in.x30in.	330 lbs.	318 lbs.	NEMA L15-30P, NEM
			8.0/460V, 3Ø, 11.5A					30-amp plug 50-a
CW-3005-0ME1	3000	4.8	10.0/230V, 1Ø, 37.5A	NEMA 6-50P	45.5in.x32.5in.x30in.	470 lbs.	396 lbs.	
CW-3005-0ME3*	3000	4.8	10.0/230V, 3Ø, 25.6A or	NEMA 15-50P	45.5in.x32.5in.x30in.	450 lbs.	376 lbs.	
			10.0/460V, 3Ø, 12.8A					
CW-3006-4ME3*	3000	5.7	15.0/230V, 3Ø, 40.0A or	NEMA 15-50P	45.5in.x32.5in.x30in.	505 lbs.	431 lbs.	NEMA 6-50P,
			15.0/460V, 3Ø, 20.0A					50-amp plug
CW-4004-0ME3*	4000	3.9	15.0/230V, 3Ø, 40.0A or	NEMA 15-50P	45.5in.x32.5in.x30in.	505 lbs.	431 lbs.	
			15.0/460V, 3Ø, 20.0A					
CW-5004-0ME3*	5000	4.0	15.0/230V, 3Ø, 40.0A or	NEMA 15-50P	45.5in.x32.5in.x30in.	505 lbs.	431 lbs.	
			15.0/460V, 3Ø, 20.0A					
	+ 10	017	a suellable as us and anti-					





\*460V motors available as no-cost options.

## Options

50-0101	nigh pressure detergent injection - nigh pressure water mixes with detergent to clean even
	the heaviest build-up
AW-8400-0021	Low pressure detergent injection - Allows the user to apply the recommended detergents
CX-0003	460V, 3-Phase models - For when you have 460-volts of power available
CX-0005	Insulated dual lance - Has both a high and low pressure tip that allows you to switch to the low pressure chemical injector without having to change tips
OV 0057	
CX-0057	460V, 3-Phase models - For when you have 460-volts of power available
CX-0062	460V, 3-Phase models - For when you have 460-volts of power available
TX-1302-W	Puncture-proof tires - Tires are flat-free, maintenance-free and non-marking, 13-inch, white
	hub, two tires
	,

Model #	50-0161	AW-8400-0021	CX-0003	CX-0005	CX-0057	CX-0062	TX-1302-W
Single Phase	•	•					•
CW-2405-4ME3	•	•					•
CW-3004-4ME3	•	•	•	•			•
CW-3005-0ME3	•	•		•		•	•
CW-3006-4ME3	•	•			•		•
CW-4004-0ME3	•	•		•	•		•
CW-5004-0ME3	•	•		•	•		•

