

6000-Watt Gasoline

GEN-6000-SMHO

ChoreMaster® Series

With commitment to quality and performance, Mi-T-M ChoreMaster® generators offer great power in a compact package. They provide maximum output under any given situation and are durable and reliable.



GEN-6000-SMHO

POWERED by **HONDA**

Engine

- Honda OHV engine with low-oil shutdown
- Recoil starting system

Alternator

- Brushless 120V/240V alternator
- Total harmonic distortion (THD) less than 5%
- 100% copper windings

Frame

- Low profile, compact design
- Heavy-duty wraparound frame with 1-inch powder coated steel tubing

Components

- Fuel shut-off valve
- Fuel gauge
- Fuel tanks are powder coated outside, zinc-plated inside to prevent rusting
- Large low-tone muffler
- Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles
- Heavy-duty industrial air cleaners hold up under extreme conditions


Miscellaneous

- USDA/USFS-approved spark arrestors
- Circuit breaker protected

Warranty

- 2 year limited alternator
- 3 year limited Honda engine

Model Number	GEN-6000-SMHO
Max. AC Output	6000 watts
Rated AC Output	5500 watts
Displacement/Engine	337cc Honda OHV
Frequency/Voltage	60Hz/120V/240V
Max. Amps (120V/240V)	50.0/25.0
Cont. Amps (120V/240V)	45.8/22.9
Receptacles	(2) 120V, 20 GFCI duplex 120V/240V, 20A twist lock
Main Circuit Breakers	(2) 20A toggle circuit breaker, single pole 20A toggle circuit breaker, double pole
Rated Speed	3600 RPM
Fuel Capacity	7.3 gallons
Run Time (at full load)	6.9 hours
Dimensions (LxWxH)	28in.x24.5in.x22.25in.
Ship Wt.	228 lbs.
Net Wt.	203 lbs.



GFCI 5-20R



NEMA L14-20R
125/250V



CSA
CERTIFIED

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.

ACCESSORIES

Part Number	Description
AW-5090-0002	Lifting hook - For easier portability, folds down and out of the way when not in use
AW-5740-0013	Wheel kit - For easier portability, pneumatic tires with tubes, rubber gripped handles

